

SAMWAX® SE-936

Water-based Polyethylene Wax Emulsion

水性聚乙烯蜡乳液

Rallychem

MATERIAL SPECIFICATION:

TYPICAL PROPERTIES:

技术指标

Item	Specification
Form 外观	Light Yellow Liquid 淡黄色液体
Technical Data	
Wax Type 蜡种类	PE Wax 高熔点聚乙烯蜡
Solids Content 固含量	33.5-35.5%
Ionic Character 乳化类型	Non ionic 非离子
Melting Range 软化点	137°C
pH-Value PH 值	7-9

Properties 性能 :

- * Good stability, lubricity and softness, low foam, hydrophilicity, good feeling
良好的稳定性、润滑性和柔软性，泡沫极低，有亲水性，手感好
- * No-iron resin fibre protectant, effectively improve the tear strength of the fabric
免烫树脂纤维保护剂，有效提高织物的撕破强力
- * Yarn wet wax product, low yellowing
纱线湿上蜡产品，低黄变性

Storage 储存 :

To be stored at least 12 months under +6-28°C, to avoid frozen and temperature higher than 40°C

Dosage 用法 :

1. Yarn lubricants
Wet waxing after dyeing cotton, cellulose fibers, synthetic fibers, wool and wool blended fiber
Wax emulsion: 0.5—3% owf, Temperature: 25-40°C, Heat preservation 10-15min ,Drying
2. Easy-care resin finishing process:
Resin: 10-20g/L, Wax emulsion: 10-30g/L, Softener: 20-30g/L 120°C drying

Packaging 包装规格 :

- * 50 KG/Drum
- * 120 KG/Drum
- * 1000 KG/Drum



Shanghai Rallychem Chemicals Co., Ltd 上海瑞勒化工有限公司
17F Chang'an Building, 1001 Chang'an Road, Jing'an, Shanghai, China
上海市静安区长安路 1001 号长安大厦 17 楼

Telephone: +86-21-63173060

Web: www.rallychem.com