

RL 1002

Polyethylene Wax

聚乙烯蜡



Rallychem[®]

TYPICAL PROPERTIES:

技术指标

Property	Value
Drop Point, Mettler 熔滴点	118° C
Viscosity @ 140° C (284° F) 粘度	30 cps
Hardness @ 25° C (77° F) 针入度	3 dmm
Product Form 产品形态	White powder 白色粉末

APPLICATIONS:

RL 1002 is the PVC high-performance external lubricant to improve PVC flowability and mould post releasement. Through reducing the low melting point and increase high melting point proportion, achieves advance lubricate function and promoted post demould effect. The suitable viscosity of RL 1002 has excellent performance in the of PVC stabilizer formulation design and the PVC processing.

RL 1002 是专为提高和改善 PVC 加工流动性和后期脱模性的高性能外润滑剂。通过降低低熔点的组分比例，提高高熔点的组分比例，使之既保留前期的润滑功能，同时具备更好的后期脱模效果。RL 1002 非常适合的粘度在 PVC 稳定剂的配方设计和终端制品加工应用中有出色的表现。

- Higher average melt point 较高的平均熔点
- Excellent thermal stability to gain longer processing time 热失重小，开机时间长
- Good batch stability 批次稳定
- Better products surface gloss 制品表面光泽度好

Rallychem Chemicals

Head Office: Shanghai Rallychem Chemicals Co., Ltd

R&D Center: Jiaxing Rallychem New Material Technology Co., Ltd

Factory: Rallychem New Material (Jiangsu) Co., Ltd

Service Tel: +86-21-63173060

Service Mobil: +86-13456396233

E-mail: info@rallychem.com

瑞勒化学

营销中心: 上海瑞勒化工有限公司

研发中心: 嘉兴瑞勒新材料有限公司

生产中心: 瑞勒新材料(江苏)有限公司

客服热线: +86-21-63173060

客服热线: +86-13456396233

电子邮箱: info@rallychem.com

Website: www.rallychem.com

