

SAMWAX[®] SE-942

Rallychem

Water-based High-Melting Polyethylene Wax Emulsion

水性高熔点聚乙烯蜡乳液

MATERIAL SPECIFICATION:

TYPICAL PROPERTIES:

技术指标

Item	Specification
Form 外观	Yellow Liquid 白色液体
Technical Data	
Wax Type 蜡种类	PE Wax 高熔点聚乙烯蜡
Solids Content 固含量	40±2%
Ionic Character 乳化类型	Non ionic 非离子
Melting Range 软化点	137°C
pH-Value PH 值	6.5-7.5

Properties 性能 :

* Paint (flooring, furniture): high gloss and high feeling

色漆 (地板、家具) : 高光和手感性能, 具有较高的耐磨擦性能

* Improve performance of printing ink, varnish, aqueous varnish

有效提高或改善印刷油墨、清漆、水性上光油的性能

* Gloss, slip, scratch/ wear/ abrasion/ impact/ stain resistance

光泽、清爽性、抗刮擦及磨损性、耐擦伤、抗冲击、耐沾污

Storage 储存 :

To be stored at least 12 months under +6-28°C, to avoid frozen and temperature higher than 40°C

本产品至少可在+6-28°C下储存 12 个月以上, 避免冷冻及超过 40°C高温

Dosage 用法 :

0.5-3% in reference to impregnation method of textile industry

在纺织工业中浸渍法用量大约 0.5-3%

通过搅拌很容易被混合, 在生产后阶段加入

Packaging 包装规格 :

* 50 KG/Drum

* 120 KG/Drum

* 1000 KG/Drum



Shanghai Rallychem Chemicals Co., Ltd 上海瑞勒化工有限公司
17F Chang'an Building, 1001 Chang'an Road, Jing'an, Shanghai, China
上海市静安区长安路 1001 号长安大厦 17 楼

Telephone: +86-21-63173060

Web: www.rallychem.com