

SAMWAX® SD-906

Water-based High-Melting Polyethylene Wax Emulsion
水性高熔点聚乙烯蜡乳液

Rallychem

MATERIAL SPECIFICATION:

TYPICAL PROPERTIES:

技术指标

Item	Specification
Particle Size 粒径	2-3 μm
Wax Type 蜡种类	PE Wax 聚乙烯蜡
Solids Content 固含量	50 \pm 3%
Ionic Character 乳化类型	Nonionic 非离子
Melting Range 软化点	137 $^{\circ}\text{C}$
pH-Value PH 值	7.0-9.0

Properties 性能 :

*Gloss, slip, scratch/ wear/ abrasion/ impact/ stain resistance

滑爽性、抗刮擦及磨损性、耐擦伤、抗冲击、耐沾污

* Oil Resistance, Abrasion Resistance

耐油、高耐磨

Application 应用:

* opv's inks

光油, 油墨

* Nitrile Glove

丁腈手套

* Supported Glove

带衬里手套

Storage 储存 :

To be stored at least 12 months under +6-28 $^{\circ}\text{C}$, to avoid frozen and temperature higher than 40 $^{\circ}\text{C}$

本产品至少可在+6-28 $^{\circ}\text{C}$ 下储存 12 个月以上, 避免冷冻及超过 40 $^{\circ}\text{C}$ 高温

Packaging 包装规格 :

* 50 KG/Drum

* 120 KG/Drum

* 1000 KG/Drum



Shanghai Rallychem Chemicals Co., Ltd 上海瑞勒化工有限公司
17F Chang'an Building, 1001 Chang'an Road, Jing'an, Shanghai, China
上海市静安区长安路1001号长安大厦17楼

Telephone: +86-21-63173060

Web: www.rallychem.com