

# SAMWAX<sup>®</sup> SE-910

# Rallychem

Water-based High-Melting Polyethylene Wax Emulsion

水性高熔点聚乙烯蜡乳液

MATERIAL SPECIFICATION:

TYPICAL PROPERTIES:

技术指标

Item	Specification
Form 外观	Light Yellow Liquid 透明淡黄色液体
<b>Technical Data</b>	
Wax Type 蜡种类	PE Wax 高熔点聚乙烯蜡
Solids Content 固含量	34.5% ± 1
Ionic Character 乳化类型	Non ionic 非离子
Melting Range 软化点	137°C
pH-Value PH 值	7.0
Particle size 粒径	200 nm

## Properties 性能 :

\* Paint (flooring, furniture): high gloss and high feeling

色漆 ( 地板、家具 ): 高光和手感性能

\* Improve performance of printing ink, leather finishing agent, varnish, aqueous varnish

有效提高或改善印刷油墨、皮革涂饰剂、清漆、水性上光油的性能

\* Gloss, slip, scratch/ wear/ abrasion/ impact/ stain resistance

光泽、清爽性、抗刮擦及磨损性、耐擦伤、抗冲击、耐沾污

## Storage 储存 :

To be stored at least 12 months under +6-28°C, to avoid frozen and temperature higher than 40°C

本产品至少可在+6-28°C下储存 12 个月以上，避免冷冻及超过 40°C高温

## Dosage 用法 :

4-10% in reference to the entire formulation

添加量为总配方的 4-10%，通过搅拌很容易被混合，在生产后阶段加入

## Packaging 包装规格 :

\* 50 KG/Drum

\* 120 KG/Drum

\* 1000 KG/Drum



Shanghai Rallychem Chemicals Co., Ltd 上海瑞勒化工有限公司  
17F Chang'an Building, 1001 Chang'an Road, Jing'an, Shanghai, China  
上海市静安区长安路 1001 号长安大厦 17 楼

Telephone: +86-21-63173060

Web: www.rallychem.com