

RL 916

High-Density Oxidized Polyethylene Homopolymer

高密度氧化聚乙烯均聚物



MATERIAL SPECIFICATION:

TYPICAL PROPERTIES:

技术指标

Property	Value
Acid Number 酸值	17 mg KOH/g
Hardness @ 25° C (77° F) 针入度	< 0.5 dmm
Drop Point, Mettler 滴点	140° C
Density 密度	0.99 g/cm ³
Viscosity @ 150° C (302° F) 粘度	15,000 cps

Property	RL 916
Product Form	Powder 粉末

APPLICATIONS:

PVC Cable filler, TPE process aids, hot melt adhesives, PVC processing, Emulsion

PVC 电线、电缆料, TPE 加工助剂, PVC 管件型材, PVC 发泡板, PVC 收缩膜、装饰膜, 蜡乳液

Rallychem Chemicals

Head Office: Shanghai Rallychem Chemicals Co., Ltd

R&D Center: Jiaxing Rallychem New Material Technology Co., Ltd

Factory: Rallychem New Material (Jiangsu) Co., Ltd

Service Tel: +86-21-63173060

Service Mobil: +86-13456396233

E-mail: info@rallychem.com

瑞勒化学

营销中心: 上海瑞勒化工有限公司

研发中心: 嘉兴瑞勒新材料有限公司

生产中心: 瑞勒新材料(江苏)有限公司

客服热线: +86-21-63173060

客服热线: +86-13456396233

电子邮箱: info@rallychem.com

Website: www.rallychem.com



ISO 9001:2000 Certified