

RL 200

Polyethylene Wax

聚乙烯蜡



MATERIAL SPECIFICATION:

TYPICAL PROPERTIES:

技术指标

Property	Value
Acid Number 酸值	N/A
Hardness @ 25° C (77° F) 针入度	< 4 dmm
Drop Point, Mettler 滴点	114° C
Viscosity @ 140° C (284°F) 粘度	700 cps

Property	RL 200
Product Form	Powder 粉末

APPLICATIONS:

PVC processing, Master batches, Rubber lubricant, Powder coating

PVC 加工润滑剂, 色母粒, 橡胶润滑剂, 粉末涂料

Rallychem Chemicals

Head Office: Shanghai Rallychem Chemicals Co., Ltd

R&D Center: Jiaxing Rallychem New Material Technology Co., Ltd

Factory: Rallychem New Material (Jiangsu) Co., Ltd

Service Tel: +86-21-63173060

Service Mobil: +86-13456396233

E-mail: info@rallychem.com

瑞勒化学

营销中心: 上海瑞勒化工有限公司

研发中心: 嘉兴瑞勒新材料有限公司

生产中心: 瑞勒新材料(江苏)有限公司

客服热线: +86-21-63173060

客服热线: +86-13456396233

电子邮箱: info@rallychem.com

Website: www.rallychem.com



ISO 9001:2000 Certified