

RL 32

Polyester wax

聚酯蜡

MATERIAL SPECIFICATION:

TYPICAL PROPERTIES:

技术指标

Item	Test Method	Specification
Acid Number 酸值	TMP-QCL	0-2.0 mg/KOH
Property	Value	
Drop Point, Mettler 滴点	52-56° C	
Hydroxyl value 羟值	0-5.0 mg/KOH	
Saponification Value 皂化值	108-114 mg/KOH	

Property	RL 32
Product Form	Powder 粉末
Size	100% minus 60 micron (200 micron, test method 309-OR)

APPLICATIONS:

Rigid PVC processing, PC, PA, S/B, PP
PVC 加工润滑剂, PC, PA, S/B, PP 脱模剂

OFFICE: SHANG HAI

Shanghai Rallychem Chemicals Co., Ltd
17F Chang'an Building, 1001 Chang'an Road, Jing'an, Shanghai, China
Customer Service: +86-21-63537171
E-mail: info@rallychem.com

办公地址: 上海
上海瑞勒化工有限公司
上海市静安区长安路 1001 号长安大厦 17 楼
客服热线: +86-21-63537171
电子邮箱: info@rallychem.com

WEBSITE: www.rallychem.com



Rallychem®

ISO 9001:2000 Certified