

# RL 60A

Polyester wax

聚酯蜡



**Rallychem®**

## MATERIAL SPECIFICATION:

技术指标

Property	Value
Acid Number 酸值	<7 mg KOH/g
Saponification Value 皂化值	175-205 mg KOH/g
Drop Point, Mettler 滴点	45-55° C
Density 密度	0.91 g/cm <sup>3</sup>

Property	RL 60A
Product Form	Powder 粉末

## APPLICATIONS:

PVC processing

PVC 管件型材, PVC 发泡板, 高相容性内润滑剂, 塑化性强, 耐析出

Rallychem Chemicals

Head Office: Shanghai Rallychem Chemicals Co., Ltd

R&D Center: Jiaying Rallychem New Material Technology Co., Ltd

Factory: Rallychem New Material (Jiangsu) Co., Ltd

Service Tel: +86-21-63173060

Service Mobil: +86-13456396233

E-mail: info@rallychem.com

瑞勒化学

营销中心: 上海瑞勒化工有限公司

研发中心: 嘉兴瑞勒新材料有限公司

生产中心: 瑞勒新材料(江苏)有限公司

客服热线: +86-21-63173060

客服热线: +86-13456396233

电子邮箱: info@rallychem.com

Website: www.rallychem.com



ISO 9001:2000 Certified